PEI	oved For		IED	09/30 : CIÁ		SE	RE	T	02 .		188	וס פאוט	FICE	is PROHIS
										- "	NON	AGEN	CY i	MES SA C
	YANCE COPY	1950	ED/SLOTTED		BY	_AT	<u>Z</u>		/		1		4	
		<u>'</u>	RF. FILE	VR .	SDO	2/	RS,	OH,	//eR	5	2	****	5	
AC'	TION #	F	POSR,	POER	2, 9	705A	<i></i> _				3		6	, I P
		0												 _
	T 77 31 8	3	<u> </u>			PAGE	01-01					NC Ø	11 5	7
					TOR	26 21 5	2 DE	C 73						
	OD RUEA	7 +1	a l											
	DE BUHN	HAAI	4 # 53 65	3 60 21 40										
	2NY 559		DE C 73											
	FM 5 481	€T G	& HICK AM	AFB HI										
	TO AIG			E 4 FD C									1	
			RTS BEAL TG 77.6	,C A P D U	A								2	5X1C
			W DOI KA	_	OKI									
	BT	<i>J</i>	ICKAM AF	R HT										
	SEC	₹ €	T											
	JP CC 0.		Γ.											
			SE	CTION Ø	2 OF	02 SEC	TIONS)						
		54 81	RTG SER#	K HØ 31 2						22 I				
	IT M1 09		1 88	60 x	┯╴	KUAN N				.1 19E I	NT IP CO	AH E	81. W	
						0.110			SQ N1 62		14, 4, 01		.	
	STA: ITM1 10	JK N	ID ONLY		$\overline{}$	I LIN .	A DM Y	BK S	NA RT LI	AL 4				
			RE	G :	\dashv		4 333	53 6N	11 93 62	ØE I	NT 1P CO	AH (OL W	
	CT A*)	IV N	TD ONLY	, —			UT	M: 50	SQ N4 18	3201				
	17 M1 11	1K 18	TD O NL	•		HSIN H	S IA NG	N AV	AL BAS	\$ E				
			RE	:Q:		CTY:C					NTIPC	A H C	OL W	
	ST A: U	JK N	ID ONLY	,			O I	M: 21	RV D3 3;	1,7/0				
	PART I	/•	MISS 10 N	COLLEC	TION	R ES UL T	5							
	A	, с	OLLECTIO	IN OBJEC	TIVES	SATIS	FIED							
	ITM112	L				CHING	TAO A	RM Y	BKS NE	KU	TAO			

S E C R E T
Approved For Release 2003/09/30 : CIA-RDP74B00836R000300050002-1
USAF review(s) completed.

XG DS /2

TENZAR ® Super Strength 0.5 Mil Backing	
LOW NOISE Professional Quality Oxide	
Permanent Lubrication Splice Free Polyester	
3 <u>m</u>	179 1/4 in. x 3600 ft. 6.35mm x 1100m. FOR HEAVY DUTY APPLICATIONS

A.S.U VI BOAM

intended use, and assume all risk and liability in connection therewith.

MINNESOTA MINING & MFG. CO., ST. PAUL, MINN. 55101

THE TERMS "SCOTCH", "TENZAR" AND PLAID DESIGN ARE REGISTERED TRADEMARKS OF THE 3M COMPANY.

Important Motice to Purchaser — Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. User shall determine the suitability of the product for his



3 hrs.	2 hrs.	1½ pts"	J hr.	.nim &	.nim 0£	J5 min.	.nim ¾7	291 ¾ <i>T</i>
6 hrs.	4 hrs.	3 hrs.	2 11's,	.shi 1/4.1	.nim 09	.nim DE	nim čí.	291 WE
12 hrs.	8 hrs.	6 hrs.	4 hrs.	3 hrs.	2 hrs.	141.	.nim 0E	241 % I
3600 FT.	2400 FT.	1800 FT.	1200 FT.	.TT 000	.17 00a	300 FT.	150 FT.	TIME CHARI
11 0030			TH DIREC	OB DNIC	ВЕСОВ			TIME

C-413-C	22 DEC 73
PILOT-	
BRIEF	
START: 005	
STOP: 134	
DEBRIEF	
START 138	
35010 294	
	· ·

roved For Release 2003/09/30 : CIA-RDP74B00836R000300050002-1

25X1